

RAVELLO

"A versatile leather
to withstand all
climatic conditions"

PIGMENTED LEATHER

Introducing the Ravello range, developed as a versatile leather to withstand all climatic conditions and heavy traffic. Featuring a semi matt finish and a soft silky touch, Ravello has superior abrasion and wear resistance. With additional technology, it works to protect against varying temperature, moisture and light, which will assist in reducing fade over time. This leather also can be embossed with 17 different prints or 14 different perforations. It is ideal for use in commercial and residential applications as well as public spaces and wall panelling.



WHEELMARK CERTIFICATION IMO 652



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Bovine
FINISH	Pigmented
SIZE	Average 4.8sq mtrs
THICKNESS	1.1 - 1.3mm
APPLICATION	Commercial / Residential Applications / Hospitality & High Traffic / Public Spaces & Wall Panelling
COLOUR FASTNESS TO RUBBING DRY 1500 CYCLES, WET 300 CYCLES, PERSPIRATION (ISO11640) 100 CYCLES EVALUATION ISO 105-A03 / A04	UNI EN ISO 11640: 1998 ≥ 4
COLOUR FASTNESS TO ARTIFICIAL LIGHT	UNI EN ISO 105B02 ≥ 4
FINISH ADHESION	ISO 11644 I ≥ 4 N/CM
BURNING BEHAVIOUR	FMVSS 302 I ≤ 100mm/min
TEAR STRENGTH	ISO 3377-1 I ≥ 20 N
TENSILE STRENGTH	ISO 3376 I ≥ 130 N
ARTIFICIAL AGEING - 4 HOURS @70°C	MINIMUM ≥ 4
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

AMBIENCE

“a subtle metallic leather boasting commercial and domestic applications, sophistication and elegance”

PIGMENTED LEATHER

This range of metallic leather is produced with a natural grain, created only on the best European selected hides with 16 uniquely inspired shades. The Ambience collection has a soft waxy texture with a semi-gloss surface. This finish of leather performs to the highest level of traffic in commercial and domestic applications.



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Bovine
FINISH	Pigmented (Metallic Effect)
ORIGIN	European
SIZE	Average 4.8 - 5.0sq mtrs
THICKNESS	0.9 - 1.0mm
APPLICATION	Commercial / Domestic / Wall Panels / Curtains
FIRE RATING & CERTIFICATION	BS 5852:1979 Match & Cigarette Test BS EN 1021-1-2:2006 Match & Cigarette Test
FLEXING ENDURANCE	EN ISO 5402 I > 50,000 CYCLES
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (MET.5) I ≥ 4 BLU SCALE
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640 Dry 500 ≥ 4 Wet 150 ≥ 4 Sweat 80 ≥ 4
SWEAT ALCALINE SOLUTION	EN ISO 11641 I PH8
TEAR STRENGTH, SINGLE EDGE TEAR	EN ISO 3377-1 I ≥ 20N
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

SOVEREIGN

"is a beautiful soft tanned,
waxy semi aniline with
a natural appearance"

SEMI ANILINE LEATHER

This range of leather is a beautiful soft tanned, waxy Semi Aniline with a natural appearance and is produced on only the best quality hides. Our Sovereign range is available in a multitude of elegant and vibrant colours. It is a full bodied leather thus giving a rich, supple feel. Due to the high end finish on the hides, this leather is very durable and suitable for use in high traffic areas and heavy use commercial and residential applications.



WHEELMARK CERTIFICATION



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Natural Grain Bovine
FINISH	Semi Aniline
ORIGIN	European
SIZE	4.8sq mtrs
THICKNESS	1.2 - 1.4mm
APPLICATION	Commercial / Domestic - Upholstery, Wall Panels & Curtains
FIRE RATING & CERTIFICATION	Wheelmark Blue Angel AS/NZS 1530.3:1999 AS/NZS 3837:1998 IMO 652 ISO 56601:2015 BS 5852:1979 BS EN 1021-1-2:2006 UNI EN ISO 9001: 2015 UNI EN ISO 14001:2015 CAL TB – 117 (2013. Sec.1)
COMPLIANCE TO CHEMICAL COMPOSITION (R.E.A.C.H)	ISO 17226 –1:2008 ISO 17075-2:2017 EN ISO 17234 –1:2010
FLEXING ENDURANCE	EN ISO 5402 > 50,000 CYCLES
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (MET.5) = 5 BLU SCALE
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640:1998 Dry 500 ≥ 4 Wet 250 ≥ 4 Sweat 80 ≥ 4 EN ISO 11641 Ph8
TEAR STRENGTH, SINGLE EDGE TEAR	EN ISO 3377-1 ≥ 20N
FINISH ADHESION	EN ISO 11644 ≥ 2.0 N/CM
DETERMINATION OF PH DIFFERENCE FIGURE (ONLY FOR PH < 4)	EN ISO 4045 ≥ 3.5
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

MONTE CARLO

“is a range which is bright and colourful, with a beautiful smooth grain texture.”

SEMI ANILINE LEATHER

Flamboyant and exciting is often used to describe Monte Carlo. The name certainly represents this wonderful range of leather. The Monte Carlo range is bright and colourful with a beautiful smooth grain texture, showcasing a huge range of vibrant colours. Boasting extreme versatility due to its high performance finish and full bodied nature, this Semi Aniline Italian leather is suitable for use in all commercial and residential high traffic applications as well as for Auto, Marine and Aviation.



BLUE ANGEL CERTIFIED



LWG GOLD RATED



CARBON FOOTPRINT
OF PRODUCT



CERTIFICATION OF RAW
MATERIAL TRACEABILITY

TYPE	Bovine
FINISH	Semi Aniline
ORIGIN	Italian
SIZE	Average 4.8sq mtrs
THICKNESS	1.2 - 1.4mm
APPLICATION	Commercial / Domestic - Upholstery, Wall Panels & Curtains
FIRE RATING & CERTIFICATION	Wheelmark AS/NZS 1530.30 AS/NZS 3837-1998 EN ISO 1021-1 & 1021-2 (No Ignition) IMO 652
FLEXING ENDURANCE	ISO 5402 I > 50,000 CYCLES
COLOUR FASTNESS TO LIGHT	ISO 105 B02 I ≥ 6 BLU SCALE
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640 Dry 1000 ≥ 4 Wet 250 ≥ 4 Sweat 250 ≥ 4
SWEAT ALCALINE SOLUTION	EN ISO 11641 PH8
TEAR STRENGTH, SINGLE EDGE TEAR	EN ISO 3377-1 I ≥ 20N
FINISH ADHESION	EN ISO 11644 I ≥ 20 N/CM
DETERMINATION OF PH DIFFERENCE FIGURE (ONLY FOR PH < 4)	EN ISO 4045 ≥ 3.5 ≤ 0.7
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

CASABLANCA

“is a beautiful soft
tanned semi aniline,
with a silky touch”

SEMI ANILINE LEATHER

This range of leather is a beautiful soft tanned Semi Aniline, produced on best quality European hides. The appearance has a semi-matt finish to it and when fully upholstered it gives a very smooth and luxurious look. Casablanca is a very durable leather which is good for use in high traffic residential and commercial applications.



WHEELMARK CERTIFICATION



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Natural Grain Bovine
FINISH	Semi Aniline
ORIGIN	European
SIZE	Average 4.6sq mtrs
THICKNESS	0.9 - 1.1mm
APPLICATION	Commercial / Domestic - Upholstery, Wall Panels & Curtains
FIRE RATING & CERTIFICATION	Wheelmark Blue Angel AS/NZS 1530.3:1999 AS/NZS 3837:1998 IMO 652 ISO 5660.1:2015 BS 5852:1979 BS EN 1021-1-2:2006 UNI EN ISO 9001: 2015 FAR A & FAR B (Available Upon Request) Environmental UNI EN ISO 14001:2015 CAL TB – 117 (2013. Sec.1)
COMPLIANCE TO CHEMICAL COMPOSITION (R.E.A.C.H)	ISO 17226–1:2008 ISO 17075-2:2017 EN ISO 17234–1:2010
FLEXING ENDURANCE	EN ISO 5402 > 50,000 Cycles
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (Met.5) ≥ 5 Blu Scale
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640:1998 Dry 500 ≥ 4 Wet 250 ≥ 4 Sweat 80 ≥ 4 EN ISO 11641 Ph8
TEAR STRENGTH, SINGLE EDGE TEAR	EN ISO 3377-1 ≥ 20N
FINISH ADHESION	EN ISO 11644 ≥ 2.0 N/Cm
DETERMINATION OF PH DIFFERENCE FIGURE (ONLY FOR PH < 4)	EN ISO 4045 ≥ 3.5
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

SUNDANCE

“is a beautiful rustic full grain leather, finished with oils and waxes.”

FULL ANILINE LEATHER

Sundance is a beautiful rustic full grain leather, finished with oils and waxes which gives this range a very natural appeal. This tannage creates a warm two tone appearance with subtle a pull-up effect. Sundance is produced on best quality European hides. Natural markings and defects may be seen and these hallmarks are part of the character of the leather.



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Natural Full Grain Bovine
FINISH	Full Aniline
ORIGIN	European
SIZE	Average 4.8sq mtrs
THICKNESS	0.9 - 1.1mm
APPLICATION	Commercial / Domestic - Upholstery, Wall Panels & Curtains
FIRE RATING & CERTIFICATION	AS/NZS 1530.3:1999 AS/NZS 3837:1998 BS EN 1021-1:2:2006 BS 5852:1979 UNI EN ISO 14001:2015 ISO 5660.1:2015 UNI EN ISO 9001: 2015
COMPLIANCE TO CHEMICAL COMPOSITION (R.E.A.C.H)	ISO 17226 -1:2008 ISO 17075-2:2017 EN ISO 17234 -1:2010
FLEXING ENDURANCE	EN ISO 5402 > 50,000 CYCLES
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (MET.5) ≥ 2 BLU SCALE
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640:1998 Dry 50 ≥ 3/4 Wet 20 ≥ 3 Sweat 20 ≥ 3 EN ISO 11641 Ph8
TEAR STRENGTH, SINGLE EDGE TEAR	EN ISO 3377-1 ≥ 20N
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

MURANO

“is an aniline leather
with rustic warm tones”

FULL ANILINE LEATHER

Murano is an aniline leather with a rustic appearance in a palette of sophisticated warm colour tones. The leather is produced on top quality European hides and is perfect for residential and commercial applications. Nature's hallmarks of heal scars, growth marks, etc will be on display evident proving the authenticity of this beautiful leather.



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Natural Full Grain Bovine
FINISH	Full Aniline
ORIGIN	European
SIZE	Average 4.8sq mtrs
THICKNESS	0.9 - 1.1mm
APPLICATION	Commercial / Domestic - Upholstery, Wall Panels & Curtains
FIRE RATING & CERTIFICATION	AS/NZS 3837-1998 EN ISO 10211-2:2006 BS 5852:1979 CAL TB-117 (2013, Sec. 1) ISO 56601-2015 UNI EN ISO 14001:2015 UNI EN ISO 9001: 2015 FAR A & FAR B (Available Upon Request)
COMPLIANCE TO CHEMICAL COMPOSITION (R.E.A.C.H)	ISO 17226 -1:2008 ISO 17075-2:2017 EN ISO 17234 -1:2010
FLEXING ENDURANCE	EN ISO 5402 > 50,000 CYCLES
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (MET.5) ≥ 3 BLU SCALE
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640:1998 Dry 50 ≥ 3 Wet 20 ≥ 3 Sweat 20 ≥ 3 EN ISO 11641 Ph8
TEAR STRENGTH, SINGLE EDGE TEAR	EN ISO 3377-1 ≥ 20N
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

LAGUNA

“is a very unique
Aniline with an aged
pull-up effect to it.”

FULL ANILINE LEATHER

The Laguna range of leathers is a very unique Aniline with an aged pull-up effect to it. The finish of this leather creates a very rustic aged look which gives a beautiful vintage expression to any environment. This range is produced on top quality European hides. The Laguna is suitable for use in Domestic and Commercial applications.



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Natural Full Grain Bovine
FINISH	Full Aniline Pull Up
ORIGIN	European
SIZE	Average 4.8sq mtrs
THICKNESS	0.9 - 11mm
APPLICATION	Commercial / Domestic - Upholstery, Wall Panels & Curtains
FIRE RATING & CERTIFICATION	AS/NZS 1530.3:1999 AS/NZS 3837:1998 EN ISO 1021-1 & 1021-2 UNI EN ISO 9001: 2015 Environmental UNI EN ISO 14001:2015 ISO 5660.1-2015 BS 5852:1979 BS EN 1021-1-2:2006
COMPLIANCE TO CHEMICAL COMPOSITION (R.E.A.C.H)	ISO 17226 -1:2008 ISO 17075-2:2017 EN ISO 17234 -1:2010
FLEXING ENDURANCE	EN ISO 5402 > 50,000 Cycles
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (Met.5) ≥ 3 Blu Scale
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640:1998 Dry 50 ≥ 3 Wet 20 ≥ 3 Sweat 20 ≥ 2 EN ISO 11641 Ph8
TEAR STRENGTH, SINGLE EDGE TEAR	EN ISO 3377-1 ≥ 20N
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

REGAL

“has a subtle two-tone finish revealing rich tones that provide this article with prestige and charm.”

FULL ANILINE LEATHER

This range of leather is finished using vacuum dryers together with oils and waxes. This treatment gives the leather its unique two-tone finish with a ‘pull up’ effect that provides this article with prestige and charm. Regal is produced on full grain best quality European hides with a waxy smooth touch and a bright aniline appearance. This aniline finish means the natural markings and defects of the hide may be evident and this is understood to be a part of the character of the leather.



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Natural Full Grain Bovine
FINISH	Full Aniline Pull Up
ORIGIN	European
SIZE	Average 4.8sq mtrs
THICKNESS	0.9 - 1.1mm
APPLICATION	Commercial / Domestic - Upholstery, Wall Panels & Curtains
FIRE RATING & CERTIFICATION	BS EN 1021-1-2:2006 BS 5852:1979 AS/NZS 3837:1998 ISO 5660-1 - 2015 UNI EN ISO 9001: 2015 UNI EN ISO 14001:2015 IMO A 652 CAL TB-117 (2013, Sec.1)
COMPLIANCE TO CHEMICAL COMPOSITION (R.E.A.C.H)	ISO 17226 -1:2008 ISO 17075-2:2017 ISO 17075-2:2017
FLEXING ENDURANCE	EN ISO 5402 > 50,000 Cycles
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (Met.5) ≥ 2 Blu Scale
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640:1998 Dry 50 ≥ 3/4 Wet 20 ≥ 3 Sweat 20 ≥ 3 EN ISO 11641 Ph8
TEAR STRENGTH, SINGLE EDGE TEAR	EN ISO 3377-1 ≥ 20N
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

PANAMA

“pure aniline natural leather”

FULL ANILINE LEATHER

Panama is pure aniline natural leather and is produced on the finest European raw material. Utilising natural oils and waxes in the drum, this leather produces a classic transparent finish with a slight pull up effect. Mineral tanned and Environmentally friendly this leather will last and age forever. Natural hallmarks in the leather and colour variation may be seen and illustrate the authenticity and purity of the leather. The Panama is suitable for use in both Domestic and Commercial applications.



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Natural Full Grain Bovine
FINISH	Aniline
ORIGIN	European
SIZE	Average 4.8sq mtrs
THICKNESS	1.2 - 1.4mm
APPLICATION	Commercial / Domestic - Upholstery, Wall Panels & Curtains
FIRE RATING & CERTIFICATION	EN ISO 1021-1-2:2006 BS 5852:1979 CAL TB-117 (2013, Sec. 1) UNI EN ISO 14001:2015 UNI EN ISO 9001: 2015
COMPLIANCE TO CHEMICAL COMPOSITION (R.E.A.C.H)	SO 17226 -1:2008 ISO 17075-2:2017 EN ISO 17234 -1:2010
FLEXING ENDURANCE	EN ISO 5402 > 50,000 CYCLES
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (MET.5) ≥ 2 BLU SCALE
COLOUR FASTNESS TO AND FRO RUBBING	EN ISO 11640:1998 Dry 50 ≥ 3
TEAR STRENGTH, SINGLE EDGE TEAR	TEAR EN ISO 3377-1 ≥ 20N
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

NORFOLK

“is a fine textured
Nubuck with an
aged effect.”

FULL ANILINE LEATHER

Finished by hand, Norfolk incorporates a vintage distressed look with a natural texture. Norfolk is produced on best quality European hides, low traffic commercial and residential applications. All defects and variation in colour within the hide and from hide to hide, are part of its natural allure. These are an intrinsic part of the leather and not considered as a fault.



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Nubuck
FINISH	Distressed Vintage Effect
ORIGIN	European
SIZE	Average 4.8 - 5.0sq mtrs
THICKNESS	0.9 - 1.1mm
APPLICATION	Low Traffic Commercial / Domestic / Curtains
FLEXING ENDURANCE	ISO 5402 50,000 CYCLES
COLOUR FASTNESS TO LIGHT	EN ISO 105 B02 (MET.5) 5 BLU SCALE ≥ 3
WET RUBBING	UNI EN ISO 11640 20 cycles - 3 grey scale
DRY RUBBING	UNI EN ISO 11640 50 cycles grey scale ¾
PERSPIRATION RUBBING	UNI EN ISO 11640 20 cycles - 3 grey scale
BURNING BEHAVIOUR TO CIGARETTE & MATCH FLAME	BS5852: 1979 BS EN1021-1-2: 2006 Pass
TEAR STRENGTH	ISO 3377-1 ≥ 20 N
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)

NUBUCK

“soft, velvet touch
and natural appearance,
sophisticated and elegant.”

FULL ANILINE LEATHER

Nubuck is an Aniline leather with a rich texture and beautiful soft touch, and offers great comfort. The possible presence of any imperfections, testify the authenticity and the natural look of a pure European aniline leather. Being an aniline leather, there will be variation in colour from delivery to delivery.



BLUE ANGEL CERTIFIED



LWG GOLD RATED

TYPE	Nabuk Finish / Natural Grain
FINISH	Aniline Dyed / Suede Finish
ORIGIN	European
SIZE	Aniline Dyed / Suede Finish
THICKNESS	1.2 - 1.4mm
APPLICATION	Low Traffic / Commercial / Domestic / Curtains
COLOUR FASTNESS TO ARTIFICIAL LIGHT	UNI EN ISO 105 B02 ≥ 2 Blu Scale
COLOUR FASTNESS TO RUBBING	UNI EN ISO 11640:1998 DRY 50 ≥ 3 UNI EN ISO 11640:1998 WET 10 ≥ 3
TEAR STRENGTH	UNI EN ISO 3377-1 ≥ 20 N
CARE INSTRUCTIONS	Vacuum regularly with soft brush. Use a damp white cloth that is colourfast and wipe regularly. Do not use detergents, solvents, abrasives. Protect from direct sunlight and heat sources. Avoid sharp objects.

[VIEW ENVIRONMENTAL ACCREDITATIONS & FULL SPECIFICATION DETAILS](#)